

LUXA 103 S360-100-12 AP WH

Item no.: 1030062



Presence and motion detectors
Ceiling installation outdoor

Description

- Passive infrared presence detector, surface-mounting
- 1 channel light (relay 230 V)
- Circular detection area 360°, Ø 12 m (113 m²) at 3 m mounting height
- Extension of the detection area by parallel switching, a maximum of 8 detectors can be connected in parallel
- Networking with wall detector theMura Slave possible
- Connection option for push-button for manual switching
- Operation as fully or semi-automatic possible
- One directional brightness measurement (mixed light measurement)
- Teach-in function, pulse function, test function, staircase lighting function
- Ready for operation immediately due to factory presetting
- Changes of values and settings are possible with potentiometers and with one of these optional remote controls:
 - App/universal remote control theSenda B
 - Service remote control theSenda P
 - Optional user remote control for manual override theSenda S/theSenda B
- Restriction of the detection range possible
- Also suitable for outdoor applications, by changing the installation location the detection range is reduced to Ø 8 m



Technical data

| LUXA 103 S360-100-12 AP WH | |
|--------------------------------|-------------------------|
| Operating voltage | 230 V AC |
| Frequency | 50 Hz |
| Stand-by consumption | ca. 0.5 W |
| Light measurement | Mixed light measurement |
| Colour | White |
| Switching output | Light |
| Installation type | Ceiling installation |
| Setting range brightness | 5 lx - 1000 lx |
| Detection angle | 360° |
| Installation height | 2.5 - 3.5 m |
| Light switch-off delay | 15 s - 30 min |
| Incandescent/halogen lamp load | 2300 W |

| LUXA 103 S360-100-12 AP WH | |
|----------------------------|--|
| Inrush current | max. 500 A / 200 µs |
| LED lamp 2-8 W | 400 W |
| LED lamp > 8 W | 400 W |
| Lamp types | Incandescent/halogen lamps, fluorescent lamps, Energy saving lamps, LEDs |
| Detection range | 113 m² (Ø 12 m 360°) |
| Detection range | Round |
| Remote controlled | ✓ |
| Ambient temperature | -25°C ... 55°C |
| Type of protection | IP 54 |

Subject to technical changes and misprints

additional information at: www.theben.de/product/1030062


The load data are determined with exemplary selected illuminants and are therefore typical data due to the large number of available products.

LUXA 103 S360-100-12 AP WH

Item no.: 1030062




Connection example



Detection range for planning applications at a temperature of 21 °C

| Mounting height (A) | Sitting (S) | Diagonally (T) | Head on to (R) |
|---------------------|-------------|----------------|----------------|
| 2.5 m | 13 m² 4 m | 78 m² 10 m | 28 m² 6 m |
| 3 m | 20 m² 5 m | 113 m² 12 m | 28 m² 6 m |
| 3.5 m | 20 m² 5 m | 78 m² 10 m | 28 m² 6 m |




LUXA 103 S360-100-12 AP WH

Item no.: 1030062

theben

Scale drawings



Accessories

theSenda P

Item no.: 9070910



theSenda S

Item no.: 9070911



theSenda B

Item no.: 9070985



Surface box LUXA 103 BK

Item no.: 9070843



Surface box LUXA 103 GR

Item no.: 9070844



Subject to technical changes and misprints

additional information at: www.theben.de/product/1030062

The load data are determined with exemplary selected illuminants and are therefore typical data due to the large number of available products.

07/04/2025

Page 3 of 3